

July 18, 2024

Wayne County Nebraska Board of Commissioners requirements for utility placement in Wayne County R.O.W. are as follows.

1. Must be placed in roadway at a depth of 3' minimum and 3' from the edge of the grass.
2. 4' under culverts less than or equal to 36". 8' under culverts greater than 36".
3. 8' under bottom of the ditch.
4. 15' under the bottom of all bridges and concrete box culverts. Bottom is defined as the bottom of the stream bed.
5. Vault boxes are to be 3' from the back edge of the R.O.W.
6. Bore under all road crossings.

If plowing/knifing fiber into road the following will apply.

1. Prior to the start of construction activities by permit, permittee shall provide Wayne County with a performance bond in the amount of \$100,000 (minimum), issued by a sound financial institution to transact business in the State of Nebraska in a form acceptable to Wayne County.
2. Permittee will repair any road damage caused by activity resulting from permit, including but not limited to repair and compaction of trenches or repair of culverts or box culverts or bridges damaged by permittee activities. Permittee will be responsible for proper compaction around vaults installed and to backfill all trenches. Wayne County reserves the right to approve vault locations within Wayne County R.O.W.
3. Permittee will be required to provide one load (approximately 30 tons) of ordinary road gravel for surfacing for each mile of the permitted route. Gravel will be hauled and applied by Wayne County forces and billed at a rate of \$30.00 per ton.